

POWER2GRID

The Hybrid Inverter of the Future



E-Mobility



Drive
System



Energy Storage
Systems



Power- and
Garden Tools



Industrial



Medical

YOUR BENEFITS

- **10kW PV and Battery inverter**
 - For all BMZ HV battery systems
 - Perfect for BMZ Hyperion LONG LIFE 20 Outdoor
- **Highly flexible**
 - 2 MPPT with wide voltage range of 200 to 850V
 - 1 Battery connector with wide voltage range of 135 to 750 V
 - Indoor and Outdoor rated
- **Back-up power integrated with 10ms UPS-level switch**
- **Easy to handle**
 - Weight of just 26 kg
 - Installation by one person
 - Hybrid inverter setup by menu or App
 - Cloud based monitoring
- **Low noise**
 - Natural convection cooling – no fan

TECHNICAL DETAILS

Input (PV-DC)

Max. generator power	15000 Wp (Summe aus PV 1 u. 2)
Max. input voltage	1000 V
PV start voltage	135 V
MPP voltage range	200 V bis 850 V
Max. input current input A / input B	15 A / 15 A
Max. short-circuit current input A / input B	20 A / 20 A
Number of independent MPP inputs / Strings per MPP input	2 / A:1; B:1

Battery connection (BAT-DC)

Battery type	all BMZ high-voltage systems
Voltage range	135 V bis 750 V
Max. charging current / max. discharging current	25 A / 25 A
Max. charging power / max. discharging power	10000 W / 10000 W

AC connection to public grid

Rated power (at 230 V, 50 Hz)	10000 W
Max. AC apparent power	11000 VA
AC rated voltage	380 V / 400 V/ 415 V, 3L + N + PE
Rated grid frequency	50 Hz / 60 Hz
Rated output current	14,5 A
Max. output current	16,5 A
Power factor at rated power / Adjustable displacement factor	1 / 0.8 capacitive to 0.8 inductive

TECHNISCHE DETAILS

Efficiency

Max. Efficiency / europ. Efficiency	98,2 % / 97,4%
-------------------------------------	----------------

AC backup connection

Rated power	10000 W
Max. AC apparent power	11000 VA
AC rated voltage	380 V / 400 V / 415 V, 3L + N + PE
AC grid frequency	50 Hz / 60 Hz
Switching time to backup operation	10 ms

Protective devices

Input-side disconnection point (PV-DC)	•
Ground fault monitoring / Grid monitoring	• / •
DC reverse polarity protection / AC short-circuit strength / galvanically isolated	• / • / —
All-current sensitive residual current monitoring unit	•
Protection class	I
Overvoltage category grid / PV	III / II

General data

Dimensions (W / H / D)	534 mm / 418 mm / 210 mm
Weight	26 kg
Operating temperature range	-30 °C bis +60 °C
Noise emission (typical)	< 25 dB
Self-consumption (standby)	< 15 W
Topology / Cooling concept	Transformerless / natural convection
Protection type	IP65
Permissible max. value for relative humidity (non-condensing)	100%
Connections, Interfaces	CAN, RS485, Wi-Fi and LAN connection

Sie haben Fragen?

Kontaktieren Sie uns, wir beraten Sie gerne.

Headquarter

BMZ Germany GmbH

Zeche Gustav 1
63791 Karlstein am Main
Deutschland

T: +49 6188-9956-0

E: mail@bmz-group.com

BMZ USA Inc.

1429 Miller Store Road
Virginia Beach
VA 23455
USA

T: +1-757 821-8494

E: contact-usa@bmz-group.com

BMZ Company Ltd.

Julong Technology Building B
Cuibao Road, Longgang District,
Shenzhen, Guangdong Province
P.R.China 518116

T: +86 755 8977 5800

E: contact.cn@bmz-group.com

BMZ Poland Sp. z o.o.

Alberta Einsteina 9
44-109 Gliwice
Polen

T: +48 327842 450

E: BMZPolandSales@bmz-group.com

BMZ Innovation Group Ltd

Future Business Centre
Kings Hedges Road
Cambridge, CB4 2HY
United Kingdom

T: +44 7391 351787

E: lukas.gazda@bmz-group.com

BMZ Japan KK

Shitaya 1-6-5, Taito-ku,
Tokyo, 110-0004
Japan

T: +81 35811 1973

E: tokio.kobayashi@bmz-group.com

BMZ France S.A.R.L.

153 Boulevard Haussmann
75008 Paris
Frankreich

T: +33 06 84 52 76 29

E: valerie.halais@bmz-group.com

www.bmz-group.com

© BMZ 2025

Alle Rechte vorbehalten. Vorläufiges Datenblatt. Obwohl bei der Erstellung dieses Datenblatts große Sorgfalt angewandt wurde, übernimmt BMZ keinerlei Verantwortung für etwaige Fehler oder Auslassungen. Alle enthaltenen Informationen können jederzeit ohne vorherige Ankündigung geändert werden.

Stand: 05.2025/V1

